

ARCHITECTURAL

GRATES + DRAINS

Code 65TiTDi

Range Threshold Grate Style Ti

Steel Grade 316

dimensions



65TiTDi **Threshold with Sub-Sill**

The 65TiTDi is a Threshold Drain for door track with sub sill tray featuring our 65mm wide Tile Insert.

For sliding and Hinged doors.

Featuring a linear stainless steel grate with concealed channel section connecting sill and sub-sill for door tracks and thresholds. Allows door sills to be drained while having internal and external floor surfaces with no step down.

Please be aware that depending on the installation environment, for a pool installation or close to a surf beach, you may need to have your

SPECIFICATIONS + DIMENSIONS

Channel Width **Channel Depth**

75mm 23mm - 53mm As Required N/A

STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Aged / Health Care Drainage **Balcony Drainage Commercial Drainage** Multi-Residential Drainage Special Needs Drainage Threshold Drainage

Suspended Slab Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 04/07/2024 (please check for updates)



Grates longer than 1500mm supplied in sections. Tile Inserts

3000mm supplied in sections with joiner. +/-2mm tolerance on

longer than 1200mm supplied in sections. Channels over

Visit **stormtech.com.au** for tools + inspiration.

stainless steel grates electropolished.

Outlet Size

Category Made-to-Length Channel Material Stainless Steel Length(s)

